



Request for Quote *Stagemaker® SR Motors*

FAX: 937-525-5130
EMAIL: equip.rfq@rmhoist.com

Company: _____

Name: _____

Phone: _____

E-mail: _____

GENERAL

Capacity: _____

Quantity: _____

Lift: _____

Speed: _____

Voltage: 208-3-60Hz 230-3-60Hz 460-3-60Hz 400-3-50Hz 115-1-60Hz

Application Type: Mobile (ex: concerts) Fixed (ex: theaters)

Suspension: Inverted (Chain up) Normal (Chain down)

Configuration: A (Direct control) B (Low voltage - 3 phase power, 115 V control)
 C (Programmable) D (Enhanced safety)
 E (VFD without controls) S (115V single phase)

ACCESSORIES

Pigtail arrangement:

- Power Length: _____ No connector Twist-lock connector
- Control Length: _____ No connector Twist-lock connector
- Power + Control Length: _____ Connector type: 7 Pin 14 Pin
- None

Pinout requirement (Specify if selecting a 7 pin connector): _____

(For R&M standard pinouts, please see the Stagemaker Technical Guide)

Pickle required: No Yes Length: _____ No connector Twist-lock connector

CONTROLLERS

For configuration B: 4 channel 8 channel 12 channel
(Must be used with twist-lock, 7 pin, or 14 pin connectors)

For configuration S: 4 channel 8 channel
(Must be used with twist-lock or 7 pin connectors)

QUOTE REQUIRED BY: _____
NOTES: