



# Request for Quote

## Spacemaster® SX Wire Rope Hoists

**FAX: 937-525-5130**  
**EMAIL: See our contact list at**  
**<http://www.rmhoist.com/contact.htm>**

Company: \_\_\_\_\_ Name: \_\_\_\_\_  
Phone: \_\_\_\_\_ E-mail: \_\_\_\_\_

### GENERAL

Capacity: \_\_\_\_\_  
Lift: \_\_\_\_\_

Suspension:  Lugmount  Footmount  Push trolley  
 Normal headroom  Low headroom  Double girder

Voltage:  460-3-60Hz  230-3-60Hz  208-3-60Hz  575-3-60Hz  Other: \_\_\_\_\_

### HOIST AND TROLLEY

Hoist speed: \_\_\_\_\_

Hoist control:  Two-speed (standard)  
 Variable speed - Open loop **OR**  Variable speed - Closed loop

Reeving:  Single-reeved  Double-reeved

Trolley speed: \_\_\_\_\_

Trolley control:  Two-speed  Variable speed (standard)

For double girder, specify: trolley gauge AND trolley rail size: \_\_\_\_\_

For single girder, specify: beam type OR flange width: \_\_\_\_\_

### CONTROLS

SOLO CONTROLS (We'll add a mainline contactor and control transformer.)

CRANE CONTROLS (The mainline and control transformer are assumed to be supplied by others.)

For Monorail →  Straight track  Curved track: Radius \_\_\_\_\_

Pendant required?  No  Yes Specify Motions: \_\_\_\_\_ Length: \_\_\_\_\_

### ENVIRONMENT AND DUTY CYCLE

Location of use:  Indoor  Outdoor  Outdoor Under Roof

Ambient temperature (Standard is 14-104° F / -10-40° C): \_\_\_\_\_

Hoist duty cycle (ASME/FEM):  H3/1Am  H4/2m  H4+/3m

Trolley duty cycle (CMAA/FEM):  Class C/2m  Class D/3m

QUOTE REQUIRED BY: \_\_\_\_\_

NOTES: