



Request for Quote

Stagemaker® Concert Hoists

FAX: 937-525-5130
EMAIL: See our contact list at
<http://www.rmhoist.com/contact.htm>

Company: _____

Name: _____

Phone: _____

E-mail: _____

GENERAL

Capacity: _____

Quantity: _____

Lift: _____

Speed: _____

Voltage: 208-3-60Hz 230-3-60Hz 460-3-60Hz 400-3-50Hz 115-1-60Hz

Application Type: Mobile (ex: concerts) Fixed (ex: theaters)

Suspension: Inverted (Chain up) Normal (Chain down)

Configuration: A (Direct control) B (Low voltage - 3 phase power, 115 V control)

C (Programmable) D (Enhanced safety)

E (VFD without controls) S (115V single phase)

ACCESSORIES

Pigtail arrangement:

- | | | | |
|--|---------------|---------------------------------------|--|
| <input type="checkbox"/> Power | Length: _____ | <input type="checkbox"/> No connector | <input type="checkbox"/> Twist-lock connector |
| <input type="checkbox"/> Control | Length: _____ | <input type="checkbox"/> No connector | <input type="checkbox"/> Twist-lock connector |
| <input type="checkbox"/> Power + Control | Length: _____ | Connector type: | <input type="checkbox"/> 7 Pin <input type="checkbox"/> 14 Pin |
| <input type="checkbox"/> None | | | |

Pinout requirement (Specify if selecting a 7 pin connector): _____
(For R&M standard pinouts, please see the Stagemaker Technical Guide)

Pickle required: No Yes Length: _____ No connector Twist-lock connector

CONTROLLERS

For configuration B: 4 channel 8 channel 12 channel
(Must be used with twist-lock, 7 pin, or 14 pin connectors)

For configuration S: 4 channel 8 channel
(Must be used with twist-lock or 7 pin connectors)

QUOTE REQUIRED BY: _____

NOTES: