



Request for Quote – Main/Aux
Spacemaster® SX Wire Rope Hoists

FAX: 937-525-5130
EMAIL: See our contact list at
<http://www.rmhoist.com>

Company: _____

Name: _____

Phone: _____

E-mail: _____

GENERAL

Crane Capacity: _____

Main Capacity: _____

Aux Capacity: _____

Main Lift: _____

Aux Lift: _____

Suspension: Single girder
 Double girder

Trolley Type: Separate trolleys
 Trailer trolley Common trolleys

Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz 575-3-60Hz Other: _____

MAIN HOIST AND TROLLEY

AUX HOIST AND TROLLEY

Hoist speed: _____

Hoist speed: _____

Hoist control: Two-speed (standard)
 VFD - Closed loop

Hoist control: Two-speed (standard)
 VFD - Closed loop

Reeving: Single-reeved
 Double-reeved

Reeving: Single-reeved
 Double-reeved

Trolley speed: _____

Trolley control: Two-speed VFD (standard)

Hook to Hook Dimension: _____

Load turning / Flipping: *(In order to flip or turn materials ALL of the following specifications must be present)*

Double-reeved Double girder top running Medium connection Max rope angle of 15°

If Double girder → Trolley gauge AND trolley rail size: _____

If Single girder → Beam type OR flange width: _____

CONTROLS

SOLO CONTROLS (mainline contactor and control transformer)

CRANE CONTROLS (mainline contactor and control transformer are supplied by others)

Pendant required? No Yes

Radio required? No Yes

Specify Motions: _____ Pendant cord Length: _____

Control Selection: I, II I + II Separate Buttons

ENVIRONMENT AND DUTY CYCLE

Location of use: Indoor Outdoor Outdoor Under Roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

Hoist duty cycle (ASME/FEM): H3/1Am H4/2m H4+/3m

Trolley duty cycle (CMAA/FEM): Class C/2m Class D/3m

QUOTE REQUIRED BY: _____

NOTES: