



Request for Quote

LK Electric Chain Hoists

FAX: 937-525-5130
EMAIL: See our contact list at
<http://www.rmhoist.com/contact.htm>

Company: _____

Name: _____

Phone: _____

E-mail: _____

GENERAL

Capacity: _____

Lift: _____

- Suspension: Top hook Lugmount Push trolley
- Motorized trolley Hand-gearred trolley Low headroom trolley
- Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz
- 575-3-60Hz 115-1-60Hz Other: _____

HOIST AND TROLLEY

Hoist speed: _____

- Hoist control: Single-speed Two-speed Variable-speed

Trolley speed: _____

- Trolley speed control: Two-speed Variable speed

Beam flange width: _____

- Beam type: Straight track Curved track: Radius: _____
- Pendant required? No Yes Length: _____
- Power cord required? No Yes Length: _____
- Flat cord Round cord

ENVIRONMENT AND DUTY CYCLE

- Location of use: Indoor Outdoor Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

- Hoist duty cycle (ASME/FEM): H3/1Am H4/2m

QUOTE REQUIRED BY: _____

NOTES: