



Request for Quote Spacemaster® Rope Hoists

FAX: 937-525-5130
EMAIL: equip.rfq@rmhoist.com

Company: _____

Name: _____

Phone: _____

Email: _____

GENERAL

Capacity: _____

Lift: _____

Suspension: Lugmount Footmount Push trolley

Normal headroom Low headroom Double girder

Voltage: 460-3-60Hz 230-3-60Hz 208-3-60Hz 575-3-60Hz Other: _____

HOIST AND TROLLEY

Hoist speed: _____

Hoist control: Two-speed (standard)

Variable speed → Open loop **OR** Closed loop

Reeving: Single-reeved Double-reeved

Rope Type: Wire Rope Synthetic Rope

Trolley speed: _____

Trolley control: Two speed Variable speed

For double girder, specify: trolley gauge AND trolley rail size: _____

For single girder, specify: beam type OR flange width: _____

CONTROLS

SOLO CONTROLS (We'll add a mainline contactor and control transformer.)

CRANE CONTROLS (The mainline and control transformer are assumed to be supplied by others.)

For Monorail → Straight track Curved track: Radius: _____

Pendant required? No Yes Specify Motions: _____ Length: _____

ENVIRONMENT AND DUTY CYCLE

Location of use: Indoor Outdoor Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): _____

Hoist duty cycle (ASME/FEM): H3/1Am H4/2m H4+/3m

Trolley duty cycle (CMAA/FEM): Class C/2m Class D/3m

QUOTE REQUIRED BY: _____
NOTES: