
## **RSN11 END TRUCK**

## For single and double girder cranes




The wheel loads listed are only a guideline. The max. wheel load listed is based on the structural integrity of the frame and load placement, and it does not take into account permissible wheel loading or bearing life. SG load placement is at the center, and DG load placement is for a trolley gage of 1200 mm [47 1/4\*].

The permissible dynamic wheel load listed is based on assumptions that the bridge speed is 40 m/min [130 fpm], end truck duty is Fem 2m, and the runway rail as listed.

The actual wheel load should not exceed the permissible wheel load. If the permissible dynamic wheel load is greater than the maximum dyn wheel load, then the actual wheel load cannot exceed maximum dyn wheel load.

Dynamic wheel = 1.15 x static wheel load



D004907-A 1

132

103(+0.8

			SG		DG		Permissible dyn wheel load			
SS	Н	H1	WT	Max dyn whl load	WT	Max dyn whl load	ASCE 30	ASCE 40	2" SQ BAR	
[mm]	[mm]	[mm]	[kg]	[kN]	[kg]	[kN]	[kN]	[kN]	[kN]	
1600	253	15	153	46	179	46	27.7	31.9	40.9	
2000	253	15	176	46	202	46	27.7	31.9	40.9	
2500	253	15	204	46	230	46	27.7	31.9	40.9	
3150	253	15	241	46	267	46	27.7	31.9	40.9	

L = SS + 276 + 2\*L1

Available only with ductile iron wheel.

UU = 52...82

End truck is compatible with the GES3 gear motor and can be equipped with a second gear motor when requested.

If the crane speed is faster, the duty group is more severe, or the actual runway rail is narrower, then the maximum allowable dynamic wheel load must be re-evaluated.

!	Suitable buffers						
Code	D1 [mm]	L1 [mm]					
Α	63	53					
В	80	68					
С	100	85					
K	80	80 100					
G	100						
E	100	150					
A, B, C: Rubber							
K,G,E: Polyurethane							

2007-03-27

EBN11

- 1	<u> </u>										
						ETTVPH	ETTVPH			EBN11	
						Design	Chd	Appd	Ref Drawing	LBINITI	
					2007-03-27	END TRUCK ∈				€	
						Date	END IRUCI	`			LIA A
- h	rv.	Explanation	Date Revised by	Checked by	SLEQDOCV	RSN11				1:6	
L		axplanation		Neviaed by	Checked by	Owner Dept	KSIVII				Folder
	This document is the absolute property of R&M Materials Handling, Inc.										EBN11
	Into accument is the adsolute property on Kown Materials Handling, Inc. This document must not be copied without the written permission of R&M Materials Handling, Inc. The contents thereof must not be disclosed to a third party nor be used for any unauthorized oursoes. Contravention will be prosecuted.										
The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.							Issue				
	MITEMAL MANUE.								08/2025		