


Double Girder - Medium, 4 PART SINGLE
Hoist type:
SXR10 041..M

SI



Headroom C-Dimension					Notes
Case 1 (mm)	Case 2 (mm)	Case 3 (mm)	Case 4 (mm)	Case 5 (mm)	Case 1: Steel rope without HS22 limit switch
320	500	555	430	485	Case 2: Steel rope with HS22 limit switch
					Case 3: Steel rope with HS22 L.S. & Rope angle sensor
					Case 4: Synthetic rope and HS22 limit switch
					Case 5: Synthetic rope with HS22 L.S. & Rope angle sensor
					HS22 limit switch mandatory with synthetic rope

HOL	Length	H1	H2	WW min	WW max	R min	R max	Estimated weight *	
(m)	code	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)	(kg)
9	C	665	130	52	82	1200	2000	694	730
12	D	840	174	52	82	1400	2000	735	762
15	E	1025	219	52	82	1700	2000	785	794
18	F	1210	263	52	82	2000	2000	830	830

Load (kg)	Class Fem/ISO	Class ASME
5000	3m/M6	H4+
6300	3m/M6	H4+
8000	3m/M6	H4+
10000	2m/M5	H4
12500	1Am/M4	H3

* Estimated weight with P5 hoist motor
Standard rail gauges are 1200 mm, 1400 mm, 1700 mm, 2000 mm.
Default trolley gauge is R min. Dim H1 listed is based on R min.

This document is the absolute property of R&M Materials Handling, Inc. This document must not be copied without the written permission of R&M Materials Handling, Inc.
The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.

Design	Chd	Appd	Ref Drawing	R10-M-04
Date	DOUBLE GIRDER HOIST			
SLEQMECE Owner Dept	4 PART SINGLE			
R10041_M				1:10 Folder
				Issue 2

