




Normal Headroom - for Straight Track, 4 PART SINGLE
Hoist type:

US-60Hz

SXR3 041..N



Flange Width	Headroom C-Dimension				
	Case 1	Case 2	Case 3	Case 4	Case 5
B-dimension					
[inch]	[inch]	[inch]	[inch]	[inch]	[inch]
4" - 17 3/4"	27 15/16"	35 5/8"	38"	31 1/16"	36"
Case 1: Steel rope without HS22 limit switch					
Case 2: Steel rope with HS22 limit switch					
Case 3: Steel rope with HS22 L.S. & Rope angle sensor					
Case 4: Synthetic rope with HS22 limit switch					
Case 5: Synthetic rope with HS22 L.S. & Rope angle sensor					
HS22 limit switch mandatory with synthetic rope					

HOL	Length	H2	L1	Estimated Weight
(ft-in)	code	(inch)	(inch)	(lb)
21'-4"	B	3 3/4"	21 7/16"	800
29'-6"	C	5 1/4"	27 3/8"	820

Load (ton)	Class
2	H4+
2 1/2	H4+
3	H4

This document is the absolute property of R&M Materials Handling, Inc. This document must not be copied without the written permission of R&M Materials Handling, Inc. The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.

Design	Chd	Appd	Ref Drawing	R3-N-04
Date	NORMAL HEADROOM HOIST			
SLEOMECE Owner/Dept	FOR STRAIGHT TRACK			
	4 PART SINGLE			
	R3041_N			
			1:10	Folder
				Issue 1

