





Normal Headroom - Swivel Trolley for Curved Track, 4 PART SINGLE Hoist type:

US-60Hz

SXR3 041..U



Flange Width	Headroom C-Dimension				
B-dimension	Case 1	Case 2	Case 3	Case 4	Case 5
[inch]	[inch]	[inch]	[inch]	[inch]	[inch]
4" - 17 3/4"	27 15/16"	35 5/8"	38"	31 1/16"	36"
Case 1: Steel rope without HS22 limit switch					
Case 2: Steel rope with HS22 limit switch					
Case 3: Steel rope with HS22 L.S. & Rope angle sensor					
Case 4: Synthetic rope with HS22 limit switch					
Case 5: Synthetic rope with HS22 L.S. & Rope angle sensor					
HS22 limit switch mandatory with synthetic rope					

HOL	Length	H2	L1	Estimated Weight
(ft-in)	code	(inch)	(inch)	(lb)
21'-4"	B	3 3/4"	21 7/16"	481
29'-6"	C	5 1/4"	27 3/8"	503

Load	Class
(ton)	ASME
2	H4+
2 1/2	H4+
3	H4

Rev Explanation Date Revised by Checked by

This document is the absolute property of R&M Materials Handling, Inc. This document must not be copied without the written permission of R&M Materials Handling, Inc. The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.

Design	Chd	Appd	Ref Drawing	R3-U-04
Date	NORMAL HEADROOM HOIST - SWIVEL TROLLEY			
SLEOMECE Owner Dept	FOR CURVED TRACK			
4 PART SINGLE				1:10 Folder
R3041_U				Issue 1

R3-U-04_1

2025-06-24

R3-U-04