



Normal Headroom - for Straight Track, 4 PART SINGLE

Hoist type:

SXR5 041..N

SI



Flange Width	Headroom C-Dimension				
	Case 1	Case 2	Case 3	Case 4	Case 5
B-dimension					
[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
100 - 450	754	934	994	824	919
Case 1: Steel rope without HS22 limit switch					
Case 2: Steel rope with HS22 limit switch					
Case 3: Steel rope with HS22 L.S. & Rope angle sensor					
Case 4: Synthetic rope with HS22 limit switch					
Case 5: Synthetic rope with HS22 L.S. & Rope angle sensor					
HS22 limit switch mandatory with synthetic rope					

HOL	Length	H2	L1	Estimated weight
(m)	code	(mm)	(mm)	(kg)
6.5	B	92	582	481
9	C	138	734	508
12	D	184	918	521

Load	Class	Class
(kg)	Fem/ISO	ASME
3200	3m/M6	H4+
4000	3m/M6	H4+
5000	2m/M5	H4
6300	1Am/M4	H3

This document is the absolute property of R&M Materials Handling, Inc. This document must not be copied without the written permission of R&M Materials Handling, Inc. The contents thereof must not be disclosed to a third party nor be used for any unauthorized purpose. Contravention will be prosecuted.

Design	Chd	Appd	Ref Drawing	R5-N-04
Date	NORMAL HEADROOM HOIST			1:10
SLEOMECE Owner/Dept	FOR STRAIGHT TRACK			Folder
4 PART SINGLE				Issue
R5041_N				1

