


Double Girder Hoist EXSX7, REEVING: 042; Class I, Division 2



D007650-A

HOL m	HOL* m	Length code	M1 mm	M2 mm	Min R mm	Max R mm	Weight** kg
7.5	4	F	832	434	1700	2400	2650
10	6.5	G	1022	339	1700	2700	2810
13.5	10	H	1272	214	2000	3100	2940
18.5	15	J	1622	389	2400	3400	3140
23	19.5	K	1922	389	2700	3800	3290
27.5	24	L	2272	414	3100	4200	3490
31	27.5	M	2522	439	3400	4200	3640
35.5	32	N	2822	489	3800	4200	3840

\*HOL with drum brake

\*\*Presence of a drum brake increases weight by 80 kgs.

Motor Dimensions

Motor	P6
MOT (mm)	536
Weight (kg)	86

Traveling Dimensions

Motor	MF07X
Weight (kg)	13.5

Trolley Dimensions

C	ØWD	ØBU	BU	BUH	E1	E2	E3	GEA	H3	H4	M3
1220	250	100	262	150	538.2	1525.7	190.7	201	687	653	44
RO	TD	TH	WB	W min	W max						
130	20	852	1340	54	99						

D007650\_A  
252895

Note: Weight calculated with P6 and MF07X motors.

Note: All dimensions in mm.

Note: Standard rail gauges: 1700, 2000, 2400, 2700, 3100, 3400, 3800 and 4200.

Note: M2 and weight calculated with Min R.

Note: Flangeless wheels available.