



# Request for Quote Crane Packages

FAX: 937-525-5130  
EMAIL: equip.rfq@rmhoist.com

Company: \_\_\_\_\_

Name: \_\_\_\_\_

Phone: \_\_\_\_\_

E-mail: \_\_\_\_\_

### GENERAL

Type of crane:  Single girder  Double girder

End trucks:  Top running  Under running

Type of hoist:  Wire Rope  Chain

Capacity: \_\_\_\_\_

Lift: \_\_\_\_\_

Span: \_\_\_\_\_

Voltage:  460-3-60Hz  230-3-60Hz  208-3-60Hz  575-3-60Hz  Other: \_\_\_\_\_

Control:  PRQ pendant (standard)  PD pendant (optional)  Radio

Electrification:  C-track festoon  NRGmaster

### HOIST, TROLLEY & BRIDGE

Hoist speed: \_\_\_\_\_

Hoist control:  Two-speed (standard)  
 Variable speed →  Open loop **OR**  Closed loop

Reeving:  Single-reeved  Double-reeved

Trolley speed: \_\_\_\_\_  Two-speed  Variable speed (standard)  Anti-sway

Bridge speed: \_\_\_\_\_  Two-speed  Variable speed (standard)  Anti-sway

Runway rail size (top running)/ Runway beam flange (under running): \_\_\_\_\_

### ENVIRONMENT AND DUTY CYCLE

Location of use:  Indoor  Outdoor  Outdoor under roof

Ambient temperature (Standard is 14-104° F / -10-40° C): \_\_\_\_\_

Hoist duty cycle (ASME/FEM):  H3/1Am  H4/2m  H4+/3m

Trolley duty cycle (CMAA/FEM):  Class C/2m  Class D/3m

Bridge duty cycle (CMAA/FEM):  Class C/2m  Class D/3m

QUOTE REQUIRED BY: \_\_\_\_\_

NOTES: