



**Request for Quote – Main/Aux**  
**Spacemaster® SX Wire Rope Hoists**

FAX: 937-525-5130  
 EMAIL: equip.rfq@rmhoist.com

Company: \_\_\_\_\_ Name: \_\_\_\_\_

Phone: \_\_\_\_\_ E-mail: \_\_\_\_\_

**GENERAL**

Crane Capacity: \_\_\_\_\_ Main Capacity: \_\_\_\_\_ Aux Capacity: \_\_\_\_\_  
 Main Lift: \_\_\_\_\_ Aux Lift: \_\_\_\_\_

Suspension:  Single girder  Double girder  
 Trolley Type:  Separate trolleys  Trailer trolley  Common trolleys

Voltage:  460-3-60Hz  230-3-60Hz  208-3-60Hz  575-3-60Hz  Other: \_\_\_\_\_

**MAIN HOIST AND TROLLEY** **AUX HOIST AND TROLLEY**

Hoist speed: _____ Hoist control: <input type="checkbox"/> Two-speed (standard) <input type="checkbox"/> VFD - Closed loop Reeving: <input type="checkbox"/> Single-reeved <input type="checkbox"/> Double-reeved	Hoist speed: _____ Hoist control: <input type="checkbox"/> Two-speed (standard) <input type="checkbox"/> VFD - Closed loop Reeving: <input type="checkbox"/> Single-reeved <input type="checkbox"/> Double-reeved
---	---

Trolley speed: \_\_\_\_\_ Trolley control:  Two-speed  VFD (standard)

Hook to Hook Dimension: \_\_\_\_\_

Load turning / Flipping: *(In order to flip or turn materials ALL of the following specifications must be present)*  
 Double-reeved  Double girder top running  Medium connection  Max rope angle of 15°

If Double girder → Trolley gauge AND trolley rail size: \_\_\_\_\_

If Single girder → Beam type OR flange width: \_\_\_\_\_

**CONTROLS**

SOLO CONTROLS (mainline contactor and control transformer)  
 CRANE CONTROLS (mainline contactor and control transformer are supplied by others)

Pendant required?  No  Yes Radio required?  No  Yes

Specify Motions: \_\_\_\_\_ Pendant cord Length: \_\_\_\_\_

Control Selection:  I, II  I + II  Separate Buttons

**ENVIRONMENT AND DUTY CYCLE**

Location of use:  Indoor  Outdoor  Outdoor Under Roof

Ambient temperature (Standard is 14-104° F / -10-40° C): \_\_\_\_\_

Hoist duty cycle (ASME/FEM):  H3/1Am  H4/2m  H4+/3m

Trolley duty cycle (CMAA/FEM):  Class C/2m  Class D/3m

QUOTE REQUIRED BY: \_\_\_\_\_

NOTES: